

Order no.: 125121

FlexxTower single-person scaffolding

Platform height [mm]

1100 2100 3100 4100



Specification

Working height 3.1 m	Scaffolding height 2.3 m	Platform height 1.1 m	Platform width 600 mm	Platform length 1.2 m
Load capacity 2 kN/m²	Weight 69 kg	Transport dimensions 1400 x 800 x 600 mm, 69 kg	Business division MUNK Günzburger Steigtechnik	Article no. 125121
Price € 2,454.00				

Facts

- Mobile scaffolding made of sturdy aluminium tubing with welded frame parts
- For lower workplaces, the scaffolding can also be assembled at lower heights
- Can be quickly and safely assembled and disassembled by just one person (used by two) using the 3-T method from level to level
- Tool-free assembly thanks to push-fit connectors and quick-release connectors

- Easy to handle thanks to individual lightweight parts
- Space-saving transport and storage, as individual parts can be stacked compactly into each other and used as a trolley
- Excellent flexibility and stability, thanks to fold-out triangular outrigger with swivel base – also ideal for wall mounting or moving in narrow passages
- Four Ø 125 mm swivel castors with centric load application and spindles
- Aluminium toe boards and powder-coated railing frames with integrated knee rail as a safety railing
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Flexible basis

- Castors Ø 125 mm with locking device
- Height adjustment for levelling

Safe standing

- Folding triangular outrigger with swivel foot
- Also ideal for setting up against the wall or for transporting through narrow passages
- Simple to use



Quickly and safely at a height

- Simple one-person assembly and disassembly from level to level (use by up to two people)
- Practical console for ladder simplifies transport and assembly of the individual components
- Users are now always in a safe place with the 3-T method

Tool-free assembly and ease of transport

The new one-person FlexxTower scaffolding impresses with its robustness and quality, but can also be simply, quickly and safely assembled, thanks to the 3 T method (Through The Trapdoor). Users are always in a safe place, thanks to the pre-assembled double railings.

Quick-release fasteners and scaffolding claws provide added efficiency and safety during assembly, just like the practical suspended brackets for the transport of practical and lightweight aluminium components from level to level.

A trolley can also be constructed from a few components, again without the need for tools, in which the remaining scaffolding parts or even other materials can be quickly and ergonomically transported. And, thanks to its compact dimensions, the FlexxTower also fits through most doorways and can be transported in many commercial vehicles.

Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant




Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Accessories




Order no.: 012909
FlexxTower
stairway kit 1




Order no.: 012910
FlexxTower
stairway kit 2




Order no.: 012956
Components,
accessories and
spare parts



Order no.: 012955
FlexxTower double
railing



Order no.: 012905
FlexxTower push-
fit frame



Order no.: 012913
FlexxTower toe
board, front



Order no.: 012943
FlexxTower toe
board, long side



Order no.: 012931
FlexxTower
platform with
trapdoor




Order no.: 012926
FlexxTower
triangular
outrigger



Order no.: 012973
FlexxTower swivel
castor Ø 125 mm




Order no.: 012908
FlexxTower spindle
foot



Order no.: 019081
Clip tray for tubes



Order no.: 070506
Frame extension
can be clamped on



Order no.: 027912
Ballast weight



Order no.: 019274
Storage tray 500 x
220 mm



Order no.: 019276

Storage tray 800 x
300 mm



Order no.: 019176

Inventory sticker



Order no.: 019175

Inspection sticker

Corporate certifications

on sustainability criteria

