

Order no.: 125132

## FlexxTower SG

Platform height [mm]

2100

3100

4100



## Specification

|  |                                    |   |  |                                 |
|--|------------------------------------|---|--|---------------------------------|
| Working height<br><b>4.1 m</b>             | Scaffolding height<br><b>3.3 m</b> | Platform height<br><b>2.1 m</b>                           | Platform width<br><b>600 mm</b>                          | Platform length<br><b>1.2 m</b> |
| Load capacity<br><b>2 kN/m<sup>2</sup></b> | Weight<br><b>87 kg</b>             | Transport dimensions<br><b>1650 x 800 x 750 mm, 87 kg</b> | Business division<br><b>MUNK Günzburger Steigtechnik</b> | Order no.<br><b>125132</b>      |
| Price<br><b>€ 3,399.00</b>                 |                                    |   |  |                                 |

## Facts

- Mobile scaffolding made of sturdy aluminium tubing with welded frame parts
- For lower workplaces, the scaffolding can also be assembled at lower heights
- Secured on all sides thanks to leading railing; can be assembled and dismantled from level to level by one person (can be used by up to two people)
- Tool-free assembly thanks to push-fit connectors and quick-release connectors

- Easy to handle thanks to individual lightweight parts
- Space-saving transport and storage, as individual parts can be stacked compactly into each other and used as a trolley
- Excellent flexibility and stability, thanks to fold-out triangular outrigger with swivel base – also ideal for wall mounting or moving in narrow passages
- Four Ø 125 mm swivel castors with centric load application and spindles
- Aluminium toe boards and powder-coated railing frames with integrated knee rail as a safety railing
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m<sup>2</sup>

### Scope of supply

- FlexxTower push-fit frame: 6 x
- FlexxTower triangular outrigger: 4 x
- FlexxTower toe board, long side: 2 x
- FlexxTower toe board, front: 2 x
- Components, accessories and spare parts: 2 x
- FlexxTower platform with trapdoor: 1 x
- FlexxTower swivel castor Ø 125 mm: 4 x
- FlexxTower double railing: 1 x
- Instructions for assembly and use EN 1004-2 - de: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Added value

---

### Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



### Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



### Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



### Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application




### Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



### Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



### Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



This product may qualify for funding under the BG BAU Occupational Safety Subsidy! Funding is subject to conditions; the latest information can be found on the BG BAU website.

Our Safety Railing (SR) significantly reduces fall risks as an integrated edge protection system during assembly, modification, disassembly, and use of work and protective scaffolding. With this technical protection, you meet the highest safety standards while benefiting from an attractive subsidy of up to 50% of the purchase costs (maximum €100 per measure).

- ✓ For new mobile scaffolding: Safety railings are eligible for funding as part of a complete working platform (including safety railings and frame parts).
- ✓ For existing scaffolding: Retrofitting with compatible safety railings is possible.

All BG BAU members can benefit from this funding. The aim is to prevent workplace accidents, especially on construction sites, and to improve ergonomics. Detailed information from BG BAU is available at:

[www.bgbau.de/service/angebote/arbeitschutzpraemien](http://www.bgbau.de/service/angebote/arbeitschutzpraemien)

A quick guide to the funding programme and an overview of our eligible products can be found on our website under [Know-how](#).

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

