

Order no.: 125132

## FlexxTower SG

Platform height [mm]

**2100** 3100 4100



### Specification

Working height <b>4.1 m</b>	Scaffolding height <b>3.3 m</b>	Platform height <b>2.1 m</b>	Platform width <b>600 mm</b>	Platform length <b>1.2 m</b>
Load capacity <b>2 kN/m<sup>2</sup></b>	Weight <b>87 kg</b>	Transport dimensions <b>1650 x 800 x 750 mm, 87 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>	Article no. <b>125132</b>
Price <b>€ 3,310.00</b>				

### Facts

- Mobile scaffolding made of sturdy aluminium tubing with welded frame parts
- For lower workplaces, the scaffolding can also be assembled at lower heights
- Secured on all sides thanks to leading railing; can be assembled and dismantled from level to level by one person (can be used by up to two people)
- Tool-free assembly thanks to push-fit connectors and quick-release connectors

- Easy to handle thanks to individual lightweight parts
- Space-saving transport and storage, as individual parts can be stacked compactly into each other and used as a trolley
- Excellent flexibility and stability, thanks to fold-out triangular outrigger with swivel base – also ideal for wall mounting or moving in narrow passages
- Four Ø 125 mm swivel castors with centric load application and spindles
- Aluminium toe boards and powder-coated railing frames with integrated knee rail as a safety railing
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m<sup>2</sup>

### Scope of supply

- FlexxTower push-fit frame: 6 x
- FlexxTower triangular outrigger: 4 x
- FlexxTower toe board, long side: 2 x
- FlexxTower toe board, front: 2 x
- Components, accessories and spare parts: 2 x
- FlexxTower platform with trapdoor: 1 x
- FlexxTower swivel castor Ø 125 mm: 4 x
- FlexxTower double railing: 1 x
- Instructions for assembly and use EN 1004-2 - de: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Added value

---

### Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



### Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



### Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



### Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



### Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



### Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs




### Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



## Accessories



Order no.: 012909  
FlexxTower  
stairway kit 1



Order no.: 012910  
FlexxTower  
stairway kit 2




Order no.: 012956  
Components,  
accessories and  
spare parts



Order no.: 012905  
FlexxTower push-  
fit frame



Order no.: 012943  
FlexxTower toe  
board, long side



Order no.: 012913  
FlexxTower toe  
board, front



Order no.: 012926  
FlexxTower  
triangular  
outrigger




Order no.: 012973  
FlexxTower swivel  
castor  $\varnothing$  125 mm



Order no.: 012908  
FlexxTower spindle  
foot




Order no.: 012931  
FlexxTower  
platform with  
trapdoor



Order no.: 019081  
Clip tray for tubes



Order no.: 070506  
Frame extension  
can be clamped on



Order no.: 027912  
Ballast weight



Order no.: 019274  
Storage tray 500 x  
220 mm



Order no.: 019276  
Storage tray 800 x  
300 mm



Order no.: 019176  
Inventory sticker



Order no.: 019175  
Inspection sticker

## Spare parts



Order no.: 012956  
Components,  
accessories and  
spare parts



Order no.: 012905  
FlexxTower push-  
fit frame



Order no.: 012926  
FlexxTower  
triangular  
outrigger



Order no.: 012973  
FlexxTower swivel  
castor Ø 125 mm



Order no.: 012931  
FlexxTower  
platform with  
trapdoor



## Corporate certifications

---

on sustainability criteria

