

Order no.: 068181

Roof parapet bridge V2A stainless steel



Specification

Length 1 m	Entry/Exit Roof parapet bridge	Material Stainless steel	Passage width 536 mm	Clear length 880 mm
Weight 53 kg	Transport dimensions 2220 x 1000 x 590 mm, 61.7 kg	Predecessor product 068181	Business division MUNK Günzburger Steigtechnik	Article no. 068181
Price € 2,693.00				

Facts

- With grating
- Passage width 536 mm, special widths on request
- Recommendation for the bottom end at the exit point: Adjustable wall anchors or foot plates
- Descent ladder: Length 1,220 mm, Length to be cut to size by client

Scope of supply

- Grating: 1 x
- Garde-corps: 2 x
- Descent ladder: 1 x
- Assembly kit: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning

- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All [fixed ladders / vertical ladders](#) at a glance:

- [Single-flight vertical ladders](#) in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders [on buildings](#)
- DIN 14094-1: Multiple-flight [emergency ladder systems \(emergency ladders\)](#).
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders [on machinery](#).

Accessories



Order no.: 062180

Mounting kit
ballast for parapet
crossings



Order no.: 060960

Exit railing, side



Order no.: 060962

Toe board for
lateral exit railing



Order no.: 060986

Extension spacer
mounting kit



Order no.: 060964

Exit railing, side



Order no.: 060966

Toe board for
lateral exit railing



Order no.: 060968

Exit railing, side



Order no.: 063500

Safety barrier



Order no.: 063502

Safety doors
without fall
protection rail




Order no.: 063253

Ground
attachment for
base plate



Order no.: 068253

Ground
attachment for
base plate



Order no.: 063249

Rigid wall anchor
200 mm,
galvanised steel



Order no.: 063250

Wall anchor,
adjustable, 165-
205 mm,
galvanised steel



Order no.: 063262

Wall anchor w.
Clamping bracket,
adjustable, 215-
275 mm,
galvanised steel



Order no.: 063261

Wall anchor w.
clamping bracket,
adjustable 275-
375 mm,
galvanised steel



Order no.: 063269

Wall anchor w. clamping bracket, adjustable 375-500 mm, galvanised steel



Order no.: 063270

Special wall bracket, adjustment range 500-600mm, galvanised steel



Order no.: 063271

Special wall bracket, adjustment range 600-700mm, galvanised steel



Order no.: 063272

Special wall bracket, adjustment range 700-800mm, galvanised steel



Order no.: 063273

Special wall bracket, adjustment range 800-900mm, galvanised steel



Order no.: 064270

Special wall bracket, adjustment range 500-600mm, stainless steel



Order no.: 064271

Special wall bracket, adjustment range 600-700mm, stainless steel



Order no.: 064272

Special wall bracket, adjustment range 700-800mm, stainless steel



Order no.: 064273

Special wall bracket, adjustment range 800-900mm, stainless steel



Order no.: 063257

Wall anchor U-bracket, rigid



Order no.: 063259

Wall anchor U-bracket, rigid



Order no.: 063263

Wall anchor U-bracket, adjustable, 165-205 mm, galvanised steel



Order no.: 063260

Wall anchor U-bracket, adjustable, 200-275 mm, galvanised steel



Order no.: 063267

Wall anchor U-bracket, adjustable, 275-375mm, galvanised steel



Order no.: 063275

Wall anchor U-bracket, adjustable, 375-500 mm, galvanised steel

Corporate certifications

on sustainability criteria

