



Order no.: 111007

## 3-section rope ladder with supports DIN EN 1147 photoluminescent

Rung covering

Glow (yellow luminescent)

Standard (red)

### Specification

Rescue height <b>12.2 m</b>	Intended use <b>Rescue</b>	Ladder length retracted <b>5.6 m</b>	Ladder length extended <b>14 m</b>	Setting angle <b>70 °</b>
Clear width between rungs <b>270 mm</b>	Clear width, upper ladder <b>350 mm</b>	Clear width, central ladder <b>420 mm</b>	Clear width, lower ladder <b>420 mm</b>	Outer width <b>500 mm</b>
Ladder feet <b>Steel point</b>	Depth of side-rails <b>74</b>	Step/Rung height <b>28 mm</b>	Step depth <b>29 mm</b>	Number of steps/rungs <b>3x 17 rungs</b>
Max. load capacity <b>324 kg</b>	Persons max. <b>3</b>	Material <b>Aluminium</b>	Rung covering <b>Glow (yellow luminescent)</b>	Weight <b>85 kg</b>
Transport dimensions <b>6155 x 580 x 245 mm, 85 kg</b>	Business division <b>MUNK Rettungstechnik</b>	Order no. <b>111007</b>		

### Facts

- 3-section rope-extension ladder made of aluminium
- Rescue ladder compliant with DIN EN 1147

- With rope pulley, locking hook and rope brake
- Yellow luminescent, heat-insulating and non-slip plastic covering
- Supports made of aluminium tube with steel spikes and rubber jacketing
- 4-fold edged rung-to-side-rail connection
- Corrosion-resistant fixtures made of galvanised steel
- Lower ladder with steel spikes at the base
- Upper ladder with wall wheels
- Permissible load: 324 kg / 3 people

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

