

Order no.: 011300

ML folding scaffolding

Design type

Without telescopic outrigger

With telescopic outrigger



Specification

Working height 3 m	Scaffolding height 1.88 m	Platform height 1 m	Platform width 600 mm	Platform length 1.6 m
Load capacity 1.5 kN/m²	Max. load capacity 150 kg	Weight 28.6 kg	Transport dimensions 1710 x 805 x 238 mm, 18 kg	Business division MUNK Günzburger Steigtechnik
Article no. 011300	Price € 729.00			

Facts

- Folding ladder scaffolding made of stable rectangular tube side-rails
- Folding frame with self-locking hinges
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Space-saving transport and storage
- For narrow passages in assembled condition thanks to a chassis bar width of 800 mm

- Four Ø 125 mm swivel castors with locking mechanisms
- Slip-resistant platform for secure standing
- Delivered in assemblies. Once assembled, the scaffolding can be quickly set up and dismantled without tools
- Optional telescopic outriggers for even greater stability
- Working heights up to 3.0 m
- Maximum load: 150 kg

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

