

Order no.: 167220

**Mobile scaffolding,
1.35 × 3.0 m, with
inclined ascents &
outrigger.**



Platform height [mm]

- 4470
- 6430
- 8390
- 10350

Specification

Working height 6.47 m	Scaffolding height 5.74 m	Platform height 4.47 m	Platform width 1.35 m	Platform length 3 m
Load capacity 2 kN/m²	Weight 239 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation possible & allowed	Outdoor use, central installation possible & allowed
Outdoor use, lateral installation possible & allowed	Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, indoor, lateral installation 10 kg	Ballasting of scaffolding, outdoor, central installation 0 kg	Ballasting of scaffolding, outdoor, lateral installation 160 kg
Business division MUNK Günzburger Steigtechnik	Article no. 167220	Price € 7,589.00	Notice Accessories necessary to fulfil DIN EN 1004-1:2021	

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- inclined steps from platform to platform with 100 mm deep, ribbed aluminium steps and handrail for safe ascent and descent as if on stairs

- All scaffolding parts are also available individually as spare or extension parts
- Stable and flexible thanks to folding outriggers
- Also ideal for wall mounting or moving in narrow aisles
- Access through opening in the entry frame
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Large-format work area in width of 1.35 m
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Installation and removal without tools from platform to platform thanks to push-fit connectors and quick-release fasteners
- Easy to handle thanks to individual lightweight parts
- Different platform lengths available (1.80 / 2.45 / 3.0 m)
- Working heights up to 12.35 m
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²
- In order to meet the requirements of DIN EN 1004-1:2021, this scaffold must be retrofitted
- Option 1 - Conversion to MSG: 2 protective assembly railings telescopic (027991) are required for safe assembly, dismantling and conversion
- Option 2 - Conversion to SG: Replace the railings lengthwise with safety railings for mobile scaffoldings in the appropriate scaffold length (2 pieces per platform level). Replace the guardrail frame at the front (top platform level) with railing frame SG at the front in the appropriate width. Omit the diagonal braces above the first platform

Scope of supply

- Entry frame: 1 x
- Push-fit frame, 1.35 m.: 3 x
- Railing lengthwise: 3 x
- Platform with longitudinal flap: 1 x
- Platform without flap: 2 x
- Toe board front side: 2 x
- Toe board long side: 2 x
- Inclined ascent below: 1 x
- Inclined ascent: 1 x
- Handrail for mobile scaffolding with inclined ascent: 1 x
- Top handrail for mobile scaffolding with inclined ascent: 1 x
- Diagonal brace: 2 x
- Horizontal strut: 2 x
- Triangular outrigger: 4 x
- Swivel castor with spindle: 4 x
- Step-on bracket: 1 x
- Push-fit frame, 1.35 m.: 2 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability




Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs




Everything at a glance


- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant




Accessories




Order no.: 027994
Safety railing for mobile scaffolding




Order no.: 027928
Entry frame




Order no.: 027901
Push-fit frame, 1.35 m.




Order no.: 027957
Railing lengthwise




Order no.: 027986
Platform with longitudinal flap




Order no.: 027934
Platform without flap




Order no.: 027911
Toe board front side




Order no.: 027944
Toe board long side




Order no.: 027965
Inclined ascent below




Order no.: 027966
Inclined ascent




Order no.: 027984
Handrail for mobile scaffolding with inclined ascent




Order no.: 027968
Top handrail for mobile scaffolding with inclined ascent



Order no.: 027938
Diagonal brace



Order no.: 027936
Horizontal strut



Order no.: 027926
Triangular outrigger



Order no.: 027917

Swivel castor with spindle




Order no.: 027940

Step-on bracket



Order no.: 027912

Ballast weight



Order no.: 019081

Clip tray for tubes



Order no.: 027920

Wall spacer adjustable



Order no.: 070506

Frame extension can be clamped on



Order no.: 019274

Storage tray 500 x 220 mm



Order no.: 019276

Storage tray 800 x 300 mm



Order no.: 070508

Safety door on front side



Order no.: 070522

Scaffolding connector set



Order no.: 019136

Spring clip for mobile scaffolding



Order no.: 019137

Spring clip for mobile scaffolding



Order no.: 070520

Scaffolding strut telescopic



Order no.: 027104

Height-adjustable spindle



Order no.: 027922

Swivel castor with spindle, non-marking grey



Order no.: 027921

Swivel castor with spindle, electrically conductive



Order no.: 027958

Swivel castor



Order no.: 019176

Inventory sticker



Order no.: 019175

Inspection sticker

Corporate certifications

on sustainability criteria

