



Order no.: 115508

Telescopic ladder Rescue Line 3.5 m red DIN EN 1147

Design

red, 3.5 m red, 4.1 m black

Specification

Intended use	Ladder length retracted	Ladder length extended 3.5 m	Setting angle	Outer width
Rescue	1.12 m		70 °	470 mm
Depth of side-rails	Width of side-rails	Number of steps/rungs	Max. load capacity	Persons max.
100 mm	75 mm	9 rungs	500 kg	
Material Aluminium	Rung covering Standard (red)	Weight 15 kg	Business division MUNK Rettungstechnik	Order no. 115508

Facts

- Aluminium telescopic ladder
- Rescue ladder compliant with DIN EN 1147
- Abrasion-resistant anodised triangular tube siderails (partly plastic-coated)
- With heat-insulating, non-slip plastic coating
- Variable height adjustment via intuitive telescopic function (partial heights possible)
- Integrated indication of different heights (2.0 / 2.5 / 3.0 / 3.5 m)



- Safety system for controlled retraction
- Minimises the risk of crushing and injury
- Permissible load: 324 kg / 3 people
- These products are covered by the statutory warranty

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria









