



Order no.: 120061

## Mobile container hygienic type 1

Type

**1** 2

### Specification

|                           |                            |                  |  |                              |
|---------------------------|----------------------------|------------------|--|------------------------------|
| Product type<br>1         | Length<br>1.2 m            | Width<br>800 mm  | Height<br>1.27 m                             | Max. load capacity<br>500 kg |
| Castor diameter<br>200 mm | Braking system<br>Standard | Weight<br>112 kg | Business division<br>MUNK<br>Rettungstechnik | Order no.<br>120061          |

### Facts

- Mobile container with "standard" undercarriage
- Washbasin (750 x 490 mm) made of stainless steel with swivelling tap and large draining surface
- Water inlet/outlet via quick coupling (transition piece to Storz-C, pressure reducer and waste water hose 5 m included)
- Extendable hose (1/2-inch, 20 m) on drum for water supply immediately ready for use loaded in mobile container
- 2x universal dispenser for hand disinfection and soap (Euro dispenser 500 ml)
- Paper towel dispenser made of stainless steel

- Folding refuse bag holder with plastic lid
- 2 x Eurobox (600 x 400 x 235 mm) with lid
- 1x Eurobox (600 x 400 x 285 mm) with lid
- Optionally available with food-safe hoses and continuous-flow heater
- Further sizes and versions available on request
- Optionally also available with "Quadro" and "Quadro Light" undercarriage
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip operation via continuous handle bar with non-slip and cold-insulating SoftGrip coating
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake

### Scope of supply

- Mobile container: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

