

Order no.: 110006

## Wooden hook ladder DIN EN 1147



### Specification

Intended use <b>Access</b>	Ladder length <b>4.4 m</b>	Ladder feet <b>Steel point</b>	Max. load capacity <b>150 kg</b>	Persons max. <b>1</b>
Material <b>Wood</b>	Weight <b>17 kg</b>	Transport dimensions <b>4420 x 300 x 177 mm, 17 kg</b>	Business division <b>MUNK Rettungstechnik</b>	Order no. <b>110006</b>

### Facts

- Wooden hook ladder
- Access ladder compliant with DIN EN 1147
- Side-rails made of finger-jointed pine or knot-free Oregon pine
- Rungs made of knot-free ash
- Folding hook made of galvanised steel secured with locking pin
- Spacer with rubber feet
- 10 climbing rungs firmly connected to the side-rails, 3 hook rungs and 1 deck rung

- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 108 kg / 1 person

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

