



Order no.: REF-7234179

Mobile container hazardous material pump

Specification

Business division
MUNK
Rettungstechnik

Order no.
REF-7234179

Facts

- 1x hazardous material pump
- 1x cable reel EX
- 1x hand-operated diaphragm pump
- 2x suction pipe vertical
- 2x oil barrier hose C20 m in hose compartment
- 6x suction hose C dimensionally stable
- 1x suction hose 3 m dimensionally stable
- 1x perforated aluminium box (600 x 400 x 220 mm) for storing 1x pipe bend 90°, 1x discharge pipe with stopcock, 1x adapter B/C, 1x strainer basket C, 2x adapter, 1x universal filling coupling and 3x coupling wrench
- 1x perforated aluminium box (600x400x220 mm) for storing 1x earthing set RW/GW-G and 2x earthing drum

Scope of supply

- Mobile container: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

Reference model

With our reference models, we provide you with a selection of individual roll containers to illustrate the variety and possibilities of our designs. We would also be happy to manufacture mobile containers for your needs - [please contact us!](#)

Corporate certifications

on sustainability criteria

