



Order no.: 040622

Single stepladder with nivello® traverse



Number of steps

12

14

16

18

Specification

Working height 4.3 m	Step design Steps	Number of steps/rungs 12 steps	Step width 371 mm	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection Aluminium corrugated	Ladder length 3.14 m	Inclination 70 °	Base area 1.09 m
Outer width 420 mm	Stabiliser width 930 mm	Depth of side-rails 73 mm	Width of side-rails 25 mm	Max. load capacity 150 kg
Design type To lean against	Weight 9 kg	Transport dimensions 3105 x 425 x 116 mm, 9 kg	Business division MUNK Günzburger Steigtechnik	Order no. 040622
Price € 328.00				

Facts

- Aluminium step straight ladder
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm

- 4-fold edged step-to-side-rail connection
- ergo-pad® grip area
- Step spacing: 235 mm
- Ladder width: 420 mm (without stabiliser)
- Ladder inclination: 70°
- Maximum load: 150 kg
- nivello® stabiliser with optimum width for the selected product, ensuring an extra safe stance and ascent thanks to nivello® ladder shoes with 2-axis inclination technology, working angle check and exchangeable foot plates. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality

- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point




roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

