



Order no.: 036382

# GFK stepladder with nivello® crossbeam

Number of steps

12

14

# Specification

Working height	Step design	Number of steps/rungs	Step width	Step depth
4.1 m	Steps	12 steps	370 mm	80 mm
Step/Rung distance	Ladder length	Inclination 70 °	Outer width	Stabiliser width
235 mm	3.17 m		420 mm	930 mm
Depth of side-rails	Width of side-rails	Max. load capacity	Design type	Weight
73 mm	25 mm	150 kg	To lean against	14.5 kg
Transport dimensions 3168 x 421 x 74 mm, 14.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 036382	Price € 890.00	

#### **Facts**

- Step straight ladder made of GFRP
- Side-rails and steps made of glass-fibre reinforced plastic profiles (min. 10 years ageing resistance when stored and used as intended)
- Grooved steps with a depth of 80 mm
- By using the metal suspension step, the insulation voltage is reduced to 1,000 V



- High-strength step-to-side-rail connection
- Step spacing: 235 mm
- Ladder width: 420 mm (without stabiliser)
- Stabiliser made of reinforced fibre glass with non-slip ladder shoes in optimal width for the selected product
- Maximum load: 150 kg
- Ladder inclination: 70°
- Tested according to EN 61478:2002 + A1 (2004), 6.5.1 Category 2: 60,000 V
- Note: Products with GFRP content are nonreturnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

## Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 1 x

#### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.



- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures

#### Added value

#### Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. <u>Find out</u> what makes GFRP such a special material, how we use it for ladders and where these ladders are used.





# Corporate certifications

### on sustainability criteria









