



Order no.: 036822

## GRP rung single ladder with nivello® traverse



Number of rungs

12

14

### Specification

Working height <b>4.7 m</b>	Step design <b>Rungs</b>	Number of steps/rungs <b>12 rungs</b>	Step/Rung height <b>29 mm</b>	Step depth <b>28 mm</b>
Step/Rung distance <b>280 mm</b>	Ladder length <b>3.59 m</b>	Outer width <b>420 mm</b>	Stabiliser width <b>930 mm</b>	Depth of side-rails <b>73 mm</b>
Width of side-rails <b>25 mm</b>	Max. load capacity <b>150 kg</b>	Design type <b>To lean against</b>	Weight <b>11.94 kg</b>	Transport dimensions <b>3560 x 430 x 90 mm, 11.94 kg</b>
Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>036822</b>	Price <b>€ 872.00</b>		

### Facts

- Rung straight ladder made of reinforced fibre glass
- Side-rails and rungs made of reinforced fibre glass plastic profiles (min. 10 years ageing resistance)
- Rectangular rungs grooved on both sides, 28 x 29 mm

- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Tested up to 28,000 V as per DIN EN 61478:2002 Category 1
- Stabiliser made of reinforced fibre glass with non-slip ladder shoes in optimal width for the selected product
- Note: Products with GFRP content are non-returnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

### **Scope of supply**

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

### **Information on sustainability criteria**

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

