

Order no.: 070982

## Fixed mounting aid



Number of steps

- 1
- 2
- 3
- 4
- 5



### Specification

Platform height <b>200 mm</b>	Top surface depth <b>295 mm</b>	Top surface width <b>550 mm</b>	Step/Platform surface <b>Aluminium tibial plate</b>	Non-slip class <b>R10</b>
Base area length <b>370 mm</b>	Base area width <b>590 mm</b>	Design type <b>Single-sided access   Rigid</b>	Number of steps/rungs <b>1 steps</b>	Platform included as step <b>Yes</b>
Max. load capacity <b>150 kg</b>	Material <b>Aluminium</b>	Transport dimensions <b>580 x 335 x 205 mm, 3 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>	

### Facts

- Aluminium climbing aid
- Sturdy, welded bar design
- 220 mm deep steps made of aluminium chequered plate for a secure footing
- Top tread surface: 550 x 300 mm
- Non-slip plastic shoes
- Step spacing 200 mm
- Maximum load: 150 kg

### Description

The fixed mounting aid combines stability and comfort perfectly. Designed for riders, equestrians, and stable owners, it is the ideal support for safe mounting when saddling, grooming, or riding. The non-slip aluminium tread surface (R10) ensures stability and prevents slipping – even in damp conditions.

### Key Benefits

- **Maximum Safety:** Robust aluminium construction with non-slip plastic feet for secure footing on any surface.
- **Ergonomic Design:** Comfortable step spacing and generously sized platforms ensure ease of use and promote gentle mounting, reducing strain on the horse's back.
- **Flexibility:** Various models with up to 5 steps provide the right solution for every situation, from daily care routines to use in the riding arena.

### Your Advantage

Investing in the fixed mounting aid means prioritising safety and durability. Its compact design and sustainable production ensure added value for your daily stable routines and your horse's health.

#### Scope of supply

- Platform: 1 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Sturdy designs for secure stance



### From small to large

- The right product for every application
- One-sided and two-sided variants



### Industrial grade

- Robust design for demanding applications
- Use of high-quality and high-strength materials



### Non-slip plastic shoes

- Ensure secure stance
- High impact and abrasion resistance
- Simple replacement in the event of wear



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

