

Order no.: 154348

Mobile scaffolding, 0.75 × 1.80 m, with outrigger.



Platform height [mm]

3070	4470	5590	6430	7550	8390
9510	10350				

Specification

Working height 5.07 m	Scaffolding height 5.74 m	Platform height 3.07 m	Platform width 750 mm	Platform length 1.8 m
Load capacity 2 kN/m²	Weight 110 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation possible & allowed	Outdoor use, central installation possible & allowed
Outdoor use, lateral installation possible & allowed	Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, indoor, lateral installation 0 kg	Ballasting of scaffolding, outdoor, central installation 0 kg	Ballasting of scaffolding, outdoor, lateral installation 0 kg
Predecessor product 154346, 177335	Business division MUNK Günzburger Steigtechnik	Article no. 154348	Price € 3,603.00	Notice Accessories necessary to fulfil DIN EN 1004-1:2021

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- All scaffolding parts are also available individually as spare or extension parts
- Stable and flexible thanks to folding outriggers

- Also ideal for wall mounting or moving in narrow aisles
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Can be set up and dismantled without tools thanks to push-fit connections and quick-release fasteners
- Easy to handle thanks to individual lightweight parts
- Different platform lengths available (1.80 / 2.45 / 3.0 m)
- Working heights up to 12.35 m
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²
- In order to meet the requirements of DIN EN 1004-1:2021, this scaffold must be retrofitted
- Option 1 - Conversion to MSG: 2 protective assembly railings telescopic (027991) are required for safe assembly, dismantling and conversion
- Option 2 - Conversion to SG: Replace the railings lengthwise with safety railings for mobile scaffoldings in the appropriate scaffold length (2 pieces per platform level). Replace the guardrail frame at the front (top platform level) with railing frame SG at the front in the appropriate width. Omit the diagonal braces above the first platform

Scope of supply

- Push-fit frame, 0.75 m.: 2 x
- Push-fit frame, 0.75 m.: 2 x
- Railing lengthwise: 2 x
- Platform with trapdoor: 1 x
- Toe board front side: 2 x
- Toe board long side: 2 x
- Diagonal brace: 2 x
- Horizontal strut: 2 x
- Triangular outrigger: 4 x
- Swivel castor with spindle: 4 x
- Step-on bracket: 1 x
- Push-fit frame, 0.75 m.: 2 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application




Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



Accessories



Order no.: 027992

Safety railing for mobile scaffolding



Order no.: 027904

Push-fit frame, 0.75 m.



Order no.: 027918

Push-fit frame, 0.75 m.



Order no.: 027955

Railing lengthwise



Order no.: 027931

Platform with trapdoor



Order no.: 027913

Toe board front side



Order no.: 027943

Toe board long side



Order no.: 027937

Diagonal brace



Order no.: 027935

Horizontal strut



Order no.: 027926

Triangular outrigger



Order no.: 027917

Swivel castor with spindle




Order no.: 027940

Step-on bracket



Order no.: 027912

Ballast weight




Order no.: 019081

Clip tray for tubes




Order no.: 027920


Wall spacer adjustable




Order no.: 070506
Frame extension
can be clamped on




Order no.: 019274
Storage tray 500 x
220 mm




Order no.: 019276
Storage tray 800 x
300 mm




Order no.: 019175
Inspection sticker




Order no.: 019176
Inventory sticker




Order no.: 070507
Safety door on
front side




Order no.: 070505
Scaffolding
connector set




Order no.: 019136
Spring clip for
mobile scaffolding




Order no.: 019137
Spring clip for
mobile scaffolding




Order no.: 070524
Scaffolding strut
telescopic




Order no.: 027104
Height-adjustable
spindle




Order no.: 027922
Swivel castor with
spindle, non-
marking grey



Order no.: 027921
Swivel castor with
spindle,
electrically
conductive



Order no.: 027958
Swivel castor



Order no.: 027905
Push-fit frame,
0.75 m.

Corporate certifications

on sustainability criteria

