



Order no.: 040352

Level access ladder



Number of steps

12

14

16

Specification

Step design Steps	Number of steps/rungs 12 steps	Step width 371 mm	Step depth 80 mm	Step/Rung distance 235 mm
Type of non-slip protection clip-step R13	Ladder length 3.14 m	Inclination 70 °	Base area 1.22 m	Outer width 470 mm
Stabiliser width 930 mm	Depth of side-rails 73 mm	Width of side-rails 25 mm	Max. load capacity 150 kg	Design type To hang up
Handrail length 1.3 m	Weight 16.5 kg	Transport dimensions 3000 x 420 x 300 mm, 16.5 kg	Business division MUNK Günzburger Steigtechnik	Article no. 040352
Price € 1,167.00				

Facts

- Aluminium step straight ladder
- Stable rectangular tube side-rails

- 80 mm-deep steps with clip-step R13 slip-resistant step padding
- 4-fold edged step-to-side-rail connection
- Standard stabiliser 930 mm with non-slip ladder shoes
- Two rigid exit side-rails that can be attached without tools (enclosed loose)
- Two pre-assembled handrails for safe ascent and descent
- Two pre-assembled ladder head protection beams
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Handrail (mounted): 2 x
- Exit rail: 2 x
- Ladder head protection: 2 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures




Added value

clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)




Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m


- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part




Accessories




Order no.: 019328
Accessory package "Practical aids 2"




Order no.: 019309
Accessory package "Ladder head protection, complete set"




Order no.: 019115
Bucket hook




Order no.: 019141
Information sticker for step straight ladders




Order no.: 019176
Inventory sticker




Order no.: 019175
Inspection sticker




Order no.: 019639
'roll-fix' ladder castors



Order no.: 019638
'roll-fix' ladder castors




Order no.: 019239
Push-fit exit side-rail



Order no.: 019238
Push-fit exit side-rail


Spare parts




Order no.: 019632
Stabiliser complete




Order no.: 019199
Outside shoe for cross-tube



Order no.: 019174
Information sticker for step straight ladders over 3 m with stabiliser



Order no.: 019236
Push-fit, retractable exit side-rail



Order no.: 019235
Push-fit, retractable exit side-rail

Corporate certifications

on sustainability criteria

