



Order no.: 040740

## Window cleaner's ladders

Number of steps/rungs

**5 + 7**

6 + 5 + 7

3x5 + 4

2/6 + 5 + 7

### Specification

Working height <b>5.08 m</b>	Ladder length <b>4.42 m</b>	Number of steps/rungs <b>5 + 7 steps</b>	Step depth <b>80 mm</b>	Step/Rung distance <b>263 mm</b>
Upper outer width <b>118 mm</b>	Lower outer width <b>900 mm</b>	Stabiliser width <b>900 mm</b>	Inclination <b>70 °</b>	Depth of side-rails <b>73 mm</b>
Width of side-rails <b>25 mm</b>	Max. load capacity <b>120 kg</b>	Design type <b>To lean against</b>	Weight <b>15.4 kg</b>	Transport dimensions <b>3020 x 470 x 230 mm, 15.3 kg</b>
Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>040740</b>	Price <b>€ 843.00</b>		

### Facts

- Step window cleaner's ladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm-deep steps with clip-step R13 slip-resistant step padding
- 4-fold edged step-to-side-rail connection

- Secure push-fit connection with additional hook lock
- Upper ladder with castors and abrasion-resistant contact rubber pad with wedge cut-out
- Lower ladder with nivello® stabiliser for extra stability and safe ascent (enclosed separately)
- Step spacing: 263 mm
- Ladder inclination: 70°
- Maximum load: 120 kg

### Scope of supply

- Step window cleaner's ladder lower section with nivello® stabiliser and clip-step R13: 1 x
- Step window cleaner's ladder upper section with clip-step R13: 1 x
- Instructions for use and operation: 1 x
- Stabiliser (enclosed separately): 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)


- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



The movable ladder shoe sets new standards in stability

[Learn more](#)



### **nivello® stabiliser**

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



### **roll-bar retrofit kit**

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

