



Order no.: 033806

Double-sided stepladder wood



Number of steps/rungs

2x3

2x4

2x5

2x6

2x7

2x8

Specification

Working height 2.25 m	Step design Steps + Rungs mixed	Number of steps/rungs 2x 3 steps	Step/Rung height 20 mm	Step depth 80 mm
Step/Rung distance 250 mm	Ladder length 885 mm	Total length folded 885 mm	Base spread 750 mm	Inclination 70 °
Lower outer width 480 mm	Upper outer width 430 mm	Depth of side-rails 65 mm	Width of side-rails 22 mm	Max. load capacity 150 kg
Design type Freestanding Double-sided access	Weight 5 kg	Transport dimensions 900 x 470 x 160 mm, 5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033806
Price € 138.00				

Facts

- Double-sided stepladder made of wood
- Side bars made of solid sawn coniferous wood, steps made of beech wood

- Grooved steps with a depth of 80 mm
- Die obersten beiden Sprossen aus Buche 22 x 44 mm
- Pegged step-to-side-rail connection, resulting in smooth side-rail surface
- Sturdy steel hinges
- Supplied as standard with practical bucket hook
- Spread protection through firmly screwed textile straps
- plastic transport lock at the base of the ladder
- Step spacing: 230 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- These products are covered by the statutory warranty

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting

- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures




Added value

Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

