



Order no.: 033806

# Double-sided stepladder wood



Number of steps/rungs

## Specification

Working height 2.25 m	Step design Steps + Rungs mixed	Number of steps/rungs 2x 3 steps	Step/Rung height 20 mm	Step depth 80 mm
Step/Rung distance 250 mm	Ladder length 970 mm	Total length folded 970 mm	Base spread 750 mm	Inclination 70 °
Lower outer width 480 mm	Upper outer width 430 mm	Depth of side-rails 65 mm	Width of side-rails 22 mm	Max. load capacity 150 kg
Design type Freestanding   Double-sided access	Weight 5 kg	Transport dimensions 970 x 470 x 160 mm, 5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033806
Price € 138.00				

## **Facts**

- Double-sided stepladder made of wood
- Solid softwood timber side-rails, beech steps
- Grooved steps with a depth of 80 mm



- Die obersten beiden Sprossen aus Buche 22 x 44 mm
- Pegged step-to-side-rail connection, resulting in smooth side-rail surface
- Sturdy steel hinges
- Supplied as standard with practical bucket hook
- Spread protection through firmly screwed textile straps
- plastic transport lock at the base of the ladder
- Step spacing: 230 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- These products are covered by the statutory warranty

## Scope of supply

Ladder: 1 x

### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

#### Added value

#### Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

#### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





# Corporate certifications

## on sustainability criteria









