

Order no.: 167111

Mobile scaffolding SG 1.35 × 2.45 m with inclined ascents

Platform height [mm]

2510



Specification

Working height 4.51 m	Scaffolding height 3.78 m	Platform height 2.51 m	Platform width 1.35 m	Platform length 2.45 m
Load capacity 2 kN/m²	Weight 147 kg	Transport dimensions 2850 x 1400 x 650 mm, 165 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation not possible
Outdoor use, central installation possible & allowed	Outdoor use, lateral installation not possible	Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, outdoor, central installation 140 kg	Business division MUNK Günzburger Steigtechnik
Article no. 167111	Price € 4,484.00			

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Secured all around thanks to leading railing, can be assembled and dismantled from level to level

- inclined steps from platform to platform with 100 mm deep, ribbed aluminium steps and handrail for safe ascent and descent as if on stairs
- All scaffolding parts are also available individually as spare or extension parts
- Also ideal for wall mounting or moving in narrow aisles
- Access through opening in the entry frame
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Large-format work area in width of 1.35 m
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Installation and removal without tools from platform to platform thanks to push-fit connectors and quick-release fasteners
- Easy to handle thanks to individual lightweight parts
- Different platform lengths available (1.80 / 2.45 / 3.0 m)
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²

Scope of supply

- Entry frame: 1 x
- Push-fit frame, 1.35 m.: 1 x
- Railing frame front side: 2 x
- Safety railing for mobile scaffolding: 1 x
- Railing lengthwise: 1 x
- Platform with longitudinal flap: 1 x
- Platform without flap: 1 x
- Toe board front side: 2 x
- Toe board long side: 2 x
- Diagonal brace: 1 x
- Horizontal strut: 2 x
- Swivel castor with spindle: 4 x
- Top handrail for mobile scaffolding with inclined ascent: 1 x
- Inclined ascent below: 1 x
- Step-on bracket: 1 x
- Instructions for assembly and use EN 1004-2 - de: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs


















Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant




Accessories

 <p>Order no.: 027993 Safety railing for mobile scaffolding</p>	 <p>Order no.: 027996 Railing frame front side</p>	 <p>Order no.: 027928 Entry frame</p>	 <p>Order no.: 027901 Push-fit frame, 1.35 m.</p>	 <p>Order no.: 027956 Railing lengthwise</p>
 <p>Order no.: 027985 Platform with longitudinal flap</p>	 <p>Order no.: 027930 Platform without flap</p>	 <p>Order no.: 027911 Toe board front side</p>	 <p>Order no.: 027914 Toe board long side</p>	 <p>Order no.: 027963 Inclined ascent below</p>
 <p>Order no.: 027967 Top handrail for mobile scaffolding with inclined ascent</p>	 <p>Order no.: 027908 Diagonal brace</p>	 <p>Order no.: 027907 Horizontal strut</p>	 <p>Order no.: 027917 Swivel castor with spindle</p>	 <p>Order no.: 027940 Step-on bracket</p>



Order no.: 027912
Ballast weight



Order no.: 019081
Clip tray for tubes



Order no.: 027920
Wall spacer adjustable



Order no.: 070506
Frame extension can be clamped on



Order no.: 019274
Storage tray 500 x 220 mm



Order no.: 019276
Storage tray 800 x 300 mm



Order no.: 019175
Inspection sticker



Order no.: 019176
Inventory sticker



Order no.: 019136
Spring clip for mobile scaffolding



Order no.: 070520
Scaffolding strut telescopic



Order no.: 027104
Height-adjustable spindle



Order no.: 027922
Swivel castor with spindle, non-marking grey



Order no.: 027921
Swivel castor with spindle, electrically conductive



Order no.: 027958
Swivel castor

Corporate certifications

on sustainability criteria

