



Order no.: 167121

## Mobile scaffolding SG 1.35 × 3 m with inclined ascents

Platform height [mm]

2510

### Specification

Working height <b>4.51 m</b>	Scaffolding height <b>3.78 m</b>	Platform height <b>2.51 m</b>	Platform width <b>1.35 m</b>	Platform length <b>3 m</b>
Load capacity <b>2 kN/m<sup>2</sup></b>	Weight <b>157 kg</b>	Transport dimensions <b>3550 x 1400 x 650 mm, 176 kg</b>	Indoor use, central installation <b>possible &amp; allowed</b>	Indoor use, lateral installation <b>not possible</b>
Outdoor use, central installation <b>possible &amp; allowed</b>	Outdoor use, lateral installation <b>not possible</b>	Ballasting of scaffolding, indoor, central installation <b>0 kg</b>	Ballasting of scaffolding, outdoor, central installation <b>150 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>
Article no. <b>167121</b>	Price <b>€ 4,796.00</b>			

### Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Secured all around thanks to leading railing, can be assembled and dismantled from level to level

- inclined steps from platform to platform with 100 mm deep, ribbed aluminium steps and handrail for safe ascent and descent as if on stairs
- All scaffolding parts are also available individually as spare or extension parts
- Also ideal for wall mounting or moving in narrow aisles
- Access through opening in the entry frame
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Large-format work area in width of 1.35 m
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Installation and removal without tools from platform to platform thanks to push-fit connectors and quick-release fasteners
- Easy to handle thanks to individual lightweight parts
- Different platform lengths available (1.80 / 2.45 / 3.0 m)
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m<sup>2</sup>

## Scope of supply

- Entry frame: 1 x
- Push-fit frame, 1.35 m.: 1 x
- Safety railing for mobile scaffolding: 1 x
- Railing lengthwise: 1 x
- Platform with longitudinal flap: 1 x
- Platform without flap: 1 x
- Toe board front side: 2 x
- Toe board long side: 2 x
- Diagonal brace: 1 x
- Horizontal strut: 2 x
- Swivel castor with spindle: 4 x
- Top handrail for mobile scaffolding with inclined ascent: 1 x
- Inclined ascent below: 1 x
- Step-on bracket: 1 x
- Instructions for assembly and use EN 1004-2 - de: 1 x
- Push-fit frame, 1.35 m.: 2 x

## Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



### Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



### Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



### Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



### Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



### Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs




### Everything at a glance


- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant




## Accessories




Order no.: 027994  
Safety railing for mobile scaffolding




Order no.: 027928  
Entry frame




Order no.: 027901  
Push-fit frame, 1.35 m.




Order no.: 027957  
Railing lengthwise




Order no.: 027986  
Platform with longitudinal flap




Order no.: 027934  
Platform without flap




Order no.: 027911  
Toe board front side




Order no.: 027944  
Toe board long side




Order no.: 027965  
Inclined ascent below




Order no.: 027968  
Top handrail for mobile scaffolding with inclined ascent




Order no.: 027938  
Diagonal brace




Order no.: 027936  
Horizontal strut




Order no.: 027917  
Swivel castor with spindle



Order no.: 027940  
Step-on bracket



Order no.: 027912  
Ballast weight



Order no.: 019081

Clip tray for tubes



Order no.: 027920

Wall spacer adjustable



Order no.: 070506

Frame extension can be clamped on




Order no.: 019274

Storage tray 500 x 220 mm



Order no.: 019276

Storage tray 800 x 300 mm



Order no.: 019175

Inspection sticker




Order no.: 019176

Inventory sticker



Order no.: 019136

Spring clip for mobile scaffolding



Order no.: 070520

Scaffolding strut telescopic



Order no.: 027104

Height-adjustable spindle



Order no.: 027922

Swivel castor with spindle, non-marking grey




Order no.: 027921

Swivel castor with spindle, electrically conductive



Order no.: 027958

Swivel castor



Order no.: 027902

Push-fit frame, 1.35 m.



## Corporate certifications

---

on sustainability criteria

