



Order no.: 063965

Entry and exit aids

Width [mm]

340

340

Specification

Length 505 mm	Outer width 340 mm	Height 90 mm	Material Galvanised steel	Weight 3.4 kg
Transport dimensions 510 x 340 x 90 mm, 3.4 kg	Business division MUNK Günzburger Steigtechnik	Article no. 063965	Price € 140.00	

Facts

- Attachment kit for exit steps with 250 or 300 mm gap dimensions
- For the exit step with 250 mm gap dimensions, the gap dimensions are 350 and 450 mm
- For the exit step with 300 mm gap dimensions, the gap dimensions are 400 and 500 mm
- Variable assembly through slotted holes
- Material: hot-dip galvanised steel

Scope of supply

- Step stool: 1 x
- Installation material: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning

- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All [fixed ladders / vertical ladders](#) at a glance:

- [Single-flight vertical ladders](#) in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders [on buildings](#)
- DIN 14094-1: Multiple-flight [emergency ladder systems \(emergency ladders\)](#).
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders [on machinery](#).

Corporate certifications

on sustainability criteria

