

Order no.: 062180

Mounting kit ballast for parapet crossings



Specification

| Length 450 mm | Height 149 mm | Material Plastic Aluminium | Weight 57.12 kg | Transport dimensions 450 x 450 x 149 mm, 57.12 kg |
|--|---------------------|---------------------------------|--------------------|---|
| Business division MUNK Günzburger Steigtechnik | Order no. 062180 | Price € 398.00 | | |

Facts

- Welded aluminium frames with stackable plastic weights
- For mounting on roof bridging steps and support on roof surfaces
- 1 set = 2 items
- Gradients in roofs (up to 14°/25%) can be compensated for
- Can be mounted in 2 directions
- Including 4x 12.5 kg ballast weights
- Incl. protective building mat for protecting roof surfaces



Scope of supply

Frame for attic ballast: 2 x

Installation material: 2 x

Building protection mat: 2 x

Ballast weight: 4 x

Assembly instructions: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

REACH

- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All fixed ladders / vertical ladders at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders on buildings
- DIN 14094-1: Multiple-flight emergency ladder systems (emergency ladders)
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders on machinery



Corporate certifications

on sustainability criteria









