



Order no.: 166230

ML Standard mobile scaffolding SG, 0.75 x 1.80 m

Platform height [mm]

2100 3300 4100 5300

Specification

Working height 4.1 m	Scaffolding height 3.37 m	Platform height 2.1 m	Platform width 750 mm	Platform length 1.8 m
Load capacity 2 kN/m²	Weight 77 kg	Transport dimensions 2250 x 800 x 600 mm, 75 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation not possible
Outdoor use, central installation possible & allowed	Outdoor use, lateral installation not possible	Ballasting of scaffolding, indoor, central installation 100 kg	Ballasting of scaffolding, outdoor, central installation 340 kg	Business division MUNK Günzburger Steigtechnik
Article no. 166230	Price € 2,719.00			

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Secured all around thanks to leading railing, can be assembled and dismantled from level to level
- All scaffolding parts are also available individually as spare or extension parts

- Chassis bar made of galvanised steel for easy change of location (width of chassis bar: 1,500 mm)
- Four Ø 125 mm swivel castors with locking mechanisms
- Platforms with large trapdoor
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Installation and removal without tools from platform to platform thanks to push-fit connectors and quick-release fasteners
- Easy to handle thanks to individual lightweight parts
- Working heights up to 7.2 m
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²

Scope of supply

- Push-fit frame, 0.75 m.: 2 x
- Safety railing for mobile scaffolding: 2 x
- Platform with trapdoor: 1 x
- Toe board front side: 2 x
- Toe board long side: 2 x
- Diagonal brace: 2 x
- Horizontal strut: 2 x
- Swivel castor: 4 x
- Assembly instructions and instructions for use: 1 x
- Push-fit frame, 1.35 m.: 2 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size

- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools




Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant




Accessories



Order no.: 027992
Safety railing for mobile scaffolding



Order no.: 027940
Step-on bracket



Order no.: 019081
Clip tray for tubes



Order no.: 027912
Ballast weight



Order no.: 019274
Storage tray 500 x 220 mm



Order no.: 019276
Storage tray 800 x 300 mm



Order no.: 027920
Wall spacer adjustable



Order no.: 070506
Frame extension can be clamped on



Order no.: 019136
Spring clip for mobile scaffolding



Order no.: 070524
Scaffolding strut telescopic



Order no.: 027104
Height-adjustable spindle



Order no.: 027959
Swivel castor



Order no.: 027958
Swivel castor



Order no.: 019176
Inventory sticker



Order no.: 019175
Inspection sticker



Order no.: 027902

Push-fit frame,
1.35 m.

Corporate certifications

on sustainability criteria

