



Order no.: 011153

Double-sided rung ladder



Number of rungs

2x5

2x7

2x9

Specification

Working height 2.8 m	Step design Rungs	Number of steps/rungs 2x 5 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Type of non-slip protection Aluminium corrugated	Height 1.47 m	Ladder length 1.5 m	Inclination 70 °
Lower outer width 500 mm	Depth of side-rails 58 mm	Max. load capacity 150 kg	Design type Freestanding Double-sided access	Weight 6.7 kg
Transport dimensions 1534 x 495 x 177 mm, 6.5 kg	Business division MUNK Günzburger Steigtechnik	Article no. 011153	Price € 234.00	

Facts

- Double-sided rung ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance

- nivello® ladder shoes with patented 2-axis inclination technology
- Solid, galvanised steel hinges with screw attachment
- Plastic end caps on upper side-rail end
- Spreader lock with two high-strength polyester straps
- Transport securing straps
- Rung distance: 280 mm
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

The movable ladder shoe sets new standards in stability

[Learn more](#)



Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



Industrial grade


Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories




Note: Working heights


- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)




Accessories




Order no.: 019326
Accessory package "TRBS kit"




Order no.: 019324
Accessory package "Secure footing"




Order no.: 019325
Accessory package "Secure footing outdoors"




Order no.: 019327
Accessory package "Practical aids 1"




Order no.: 019910
Hook-in step R13 for rung ladders




Order no.: 019900
Hook-in platform R13 for rung ladders




Order no.: 019213
nivello® foot plate for gratings 126 x 89 mm




Order no.: 019211
nivello® foot plate for smooth surfaces




Order no.: 019224
nivello® foot plate, claw




Order no.: 019215
nivello® inside shoe, electrically conductive




Order no.: 019219
nivello® foot plate, electrically conductive




Order no.: 019846
Screw-on castors









Order no.: 019270
Storage tray for double-sided rung ladder












Order no.: 019839
Wall-mounted ladder holder L



Order no.: 019115
Bucket hook



Spare parts



Certificates



17KFP1657-02 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-
3:2007
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK
EK5-AK1 17-
02:2017
DIN EN 131-1:2016
DIN EN 131-2:2017

Corporate certifications

on sustainability criteria

