



Order no.: 022314

## 3-section rung rope-extension ladder without stabiliser



Number of rungs

3x14

3x16

3x18

### Specification

Working height <b>10.8 m</b>	Step design <b>Rungs</b>	Number of steps/rungs <b>3x 14 rungs</b>	Step/Rung height <b>30 mm</b>	Step depth <b>30 mm</b>
Step/Rung distance <b>280 mm</b>	Retracted length <b>4.1 m</b>	Extended length <b>9.7 m</b>	Outer width <b>470 mm</b>	Depth of side-rails <b>98 mm</b>
Width of side-rails <b>25 mm</b>	Design type <b>To lean against   3-part</b>	Weight <b>43 kg</b>	Transport dimensions <b>4190 x 500 x 275 mm, 43 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>
Article no. <b>022314</b>	Price <b>€ 1,832.00</b>			

### Facts

- Rung rope-extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection

- Convenient height adjustment from rung to rung thanks to two pulleys with plastic cable
- Automatically acting locking hooks, middle and upper part adjusted separately
- Upper ladder with wall wheels
- Corrosion-resistant guide fixtures with sliding guides
- Rung distance: 280 mm
- Ladder width: 470 mm (without stabiliser)
- Maximum load: 150 kg
- nivello® ladder shoes with patented 2-axis inclination technology
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

### Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x


### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



The movable ladder shoe sets new standards in stability

[Learn more](#)



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley


















### Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths




## Accessories







Order no.: 019114  
Gutter bracket




Order no.: 019842  
Wall spacer for insulated facades




Order no.: 019100  
Wall spacer for rung ladders




Order no.: 019902  
MaxxStep step module




Order no.: 019287  
Tool bag




Order no.: 019319  
Ladder head protection, gutter




Order no.: 019310  
Ladder head protection, rung and step hole




Order no.: 019315  
Ladder head protection




Order no.: 019318  
Ladder head protection, beam




Order no.: 019101  
Exit side-rail retractable




Order no.: 019102  
Exit side-rail retractable




Order no.: 011179  
Ridge bracket



Order no.: 019280  
Attachable section "Window cleaner"



Order no.: 019940  
Ground spikes for ladders with nivello ladder shoe



Order no.: 040344  
Ladder head protection, magnet



Order no.: 019256

Guide fixture, upper, for push-up extension, rope-extension and multi-purpose ladders



Order no.: 019689

Pull-out stop for rung ladders made of aluminium



Order no.: 019176

Inventory sticker



Order no.: 019175

Inspection sticker



Order no.: 030296

Push-fit handrail for rung/step spacing 280/263 mm







Order no.: 030297

Push-fit handrail for rung/step spacing 280/263 mm



## Spare parts



## Corporate certifications

---

on sustainability criteria

