

Order no.: 032208

Folding ladder, 2-section with nivello® stabiliser



Number of rungs

2x4

2x6

2x8

Specification

Working height 3.6 m	Step design Rungs	Number of steps/rungs 2x 4 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Ladder length, two-part, straight 2.56 m	Ladder length as double-sided ladder 1.28 m	Base spread as double ladder 867 mm	Inclination 70 °
Length of ladder sections 1.12 m	Total length folded 1.28 m	Outer width 350 mm	Stabiliser width 930 mm	Depth of side-rails 58 mm
Width of side-rails 25 mm	Max. load capacity 150 kg	Weight 7.5 kg	Transport dimensions 1280 x 360 x 135 mm, 7.5 kg	Business division MUNK Günzburger Steigtechnik
Article no. 032208	Price € 237.00			

Facts

- Aluminium folding rung ladder
- Stable rectangular tube side-rails

- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a step and straight ladder
- Optimum operational safety due to six automatically locking steel hinges
- nivello® ladder shoes with patented 2-axis inclination technology
- nivello® stabiliser for extra safe stance and ascent (enclosed separately)
- Rung distance: 280 mm
- Ladder width: 350 mm (without stabiliser)
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Flexibility

- Universal and versatile use
- Compact size for transport and storage
- Upper ladder can also be used individually (up to 3.0 m)



The movable ladder shoe sets new standards in stability

[Learn more](#)



Easy handling

- Insertion hooks with lift-off protection or automatically locking steel hinges
- Optimised guidance, thanks to guide fixtures with high-strength plastic coating

Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part




roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down




Note: Working heights


- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)




Accessories




Order no.: 019326
Accessory package "TRBS kit"




Order no.: 019324
Accessory package "Secure footing"




Order no.: 019325
Accessory package "Secure footing outdoors"




Order no.: 019900
Hook-in platform R13 for rung ladders




Order no.: 019910
Hook-in step R13 for rung ladders




Order no.: 019219
nivello® foot plate, electrically conductive




Order no.: 019213
nivello® foot plate for gratings 126 x 89 mm




Order no.: 019211
nivello® foot plate for smooth surfaces



Order no.: 019209
nivello® foot plate, standard




Order no.: 019224
nivello® foot plate, claw




Order no.: 019634
'roll-bar' retrofit kit




Order no.: 019901
MaxxStep step module




Order no.: 019287
Tool bag




Order no.: 019115
Bucket hook




Order no.: 019914
Side-rail extension for ladder side-rail




Order no.: 019925
Side-rail extension
for stabiliser bar



Order no.: 019216
nivello® inside
shoe, electrically
conductive




Order no.: 019176
Inventory sticker




Order no.: 019175
Inspection sticker


Spare parts




Order no.: 019476
Automatic steel
hinge for folding
ladder



Order no.: 019609
Stabiliser
complete



Order no.: 019206
nivello® inside
shoe



Order no.: 019148
Information sticker
for folding ladders,
2-section

Certificates



17KFP2039-02 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-
3:2007
DIN EN 131-
4:2007
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK
EK5/AK1 17-
03:2017
DIN EN 131-1:2016
DIN EN 131-2:2017

Corporate certifications

on sustainability criteria

