



Order no.: 033106

## Rung straight ladder, wood without stabiliser



Number of rungs

- 6
- 8
- 10
- 12
- 14

### Specification

Working height <b>3 m</b>	Step design <b>Rungs</b>	Number of steps/rungs <b>6 rungs</b>	Step/Rung height <b>40 mm</b>	Step depth <b>21 mm</b>
Step/Rung distance <b>280 mm</b>	Ladder length <b>1.92 m</b>	Outer width <b>420 mm</b>	Depth of side-rails <b>61 mm</b>	Width of side-rails <b>27 mm</b>
Max. load capacity <b>150 kg</b>	Design type <b>To lean against</b>	Weight <b>4 kg</b>	Transport dimensions <b>1920 x 420 x 60 mm, 4 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>
Order no. <b>033106</b>	Price <b>€ 101.00</b>			

### Facts

- Rung straight ladder made of wood
- Side-rails made of finger-jointed pine or knot-free Caroline pine, rungs made of ash
- Pegged rung-to-side-rail connection, resulting in smooth side-rail surface
- Rung distance: 280 mm

- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)

### **Scope of supply**

- Ladder: 1 x

### **Information on sustainability criteria**

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths




### Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

