

Order no.: 034108

## Double-sided step ladder GFRP / aluminium



Number of steps

2x4

2x6

2x8

2x10

2x12

### Specification

Working height 2.45 m	Step design Steps	Number of steps/rungs 2x 4 steps	Step depth 80 mm	Step/Rung distance 235 mm
Type of non-slip protection Aluminium corrugated	Height 1 m	Ladder length 1.1 m	Base spread 920 mm	Inclination 70 °
Lower outer width 490 mm	Depth of side-rails 73 mm	Max. load capacity 150 kg	Design type Freestanding   Double-sided access	Weight 8 kg
Transport dimensions 1053 x 490 x 210 mm, 8 kg	Business division MUNK Günzburger Steigtechnik	Order no. 034108	Price € 437.00	

### Facts

- Double-sided stepladder made of glass-fibre reinforced plastic/aluminium
- Side-rails made of reinforced fibre glass profiles
- Grooved steps with a depth of 80 mm, made of aluminium
- 4-fold edged step-to-side-rail connection

- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- ergo-pad® grip area with clamping mechanism
- Solid, galvanised steel hinges with screw attachment
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested up to 1000 V as per DIN EN 61478:2002 Clause 6.5.1 and A1:2004 Category 1
- Note: Products with GFRP content are non-returnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

### Scope of supply

- Ladder: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems

- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories




### ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



The movable ladder shoe sets new standards in stability

[Learn more](#)



### Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



## Certificates

---



17KFP1640-02 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-3:2007  
PAK-  
ANFORDERUNG  
FÜR GS -  
ABSCHNITT  
3.1 (PAH-  
REQUIREMENT  
FOR GS - CL. 3.1)  
AFPS GS 2014:01  
PAK  
DIN EN 131-1:2016  
DIN EN 131-2:2017

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

