

Order no.: 063249

# Rigid wall anchor 200 mm, galvanised steel



## **Specification**

Wall distance 200 mm	Wall anchor <b>Single</b>	Material Galvanised steel	Weight <b>0.96 kg</b>	Transport dimensions 235 x 117 x 60 mm, 0.96 kg
Business division MUNK Günzburger Steigtechnik	Order no. <b>063249</b>	Price <b>€ 23.00</b>	Spare part for article no. <b>520105</b>	Spare part for article no. <b>520115</b>
Spare part for article no. 500125	Spare part for article no. <b>510105</b>	Spare part for article no. 510110	Spare part for article no. <b>510115</b>	Spare part for article no. 500105
Spare part for article no. <b>500110</b>	Spare part for article no. <b>500115</b>	Spare part for article no. 500120	Spare part for article no. 500100	Spare part for article no. <b>520100</b>
Spare part for article no. <b>520110</b>	Spare part for article no. <b>520120</b>	Spare part for article no. <b>520125</b>	Spare part for article no. 510120	Spare part for article no. <b>510100</b>
Spare part for article no. 510125				

### **Facts**



- Optimal stability through rigid mounting mechanism
- Galvanized steel wall bracket for enduring stability
- Stable and durable steel construction for high loads
- Wall anchor

## Scope of supply

Wall anchor: 1 x

Assembly instructions: 1 x

## Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



## More product pictures





#### Added value

#### **Optimum planning**

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



#### All fixed ladders / vertical ladders at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders on buildings
- DIN 14094-1: Multiple-flight emergency ladder systems (emergency ladders)
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders on machinery



## **Corporate certifications**

on sustainability criteria









