


Order no.: 063249

Rigid wall anchor 200
mm, galvanised steel



Specification

Wall distance 200 mm	Wall anchor Single	Material Galvanised steel	Weight 0.96 kg	Transport dimensions 235 x 117 x 60 mm, 0.96 kg
Business division MUNK Günzburger Steigtechnik	Order no. 063249	Price € 23.00	Spare part for article no. 520100	Spare part for article no. 520105
Spare part for article no. 510100	Spare part for article no. 520125	Spare part for article no. 510105	Spare part for article no. 510110	Spare part for article no. 520110
Spare part for article no. 500110	Spare part for article no. 500115	Spare part for article no. 500120	Spare part for article no. 520115	Spare part for article no. 500105
Spare part for article no. 500100	Spare part for article no. 510125	Spare part for article no. 510115	Spare part for article no. 500125	Spare part for article no. 510120
Spare part for article no. 520120				

Facts

- Optimum stability thanks to rigid mounting mechanism
- Wall anchor made of galvanised steel for long-lasting stability
- Stable and durable steel construction for high loads
- Wall anchor

Scope of supply

- Wall anchor: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

Optimum planning

- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All [fixed ladders / vertical ladders](#) at a glance:

- [Single-flight vertical ladders](#) in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders [on buildings](#)
- DIN 14094-1: Multiple-flight [emergency ladder systems \(emergency ladders\)](#)
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders [on machinery](#)

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022

