



Order no.: 065009

Entry aid, double side-rails, stainless steel

For ladder width [mm]

340 440

Specification

Outer width 340 mm	Suitable for Shaft ladders	Weight 5.5 kg	Transport dimensions 1570 x 335 x 90 mm, 5.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 065009	Price € 549.00			

Facts

- Made of pickled and passivated V4A (1.4571) stainless steel or galvanised steel
- Can be lowered, complete with fixtures for ladder side-rail, 50 x 20 mm
- For ladder widths 340 and 440 mm

Scope of supply

- Entry aid: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

-
- Corporate certification: ISO 9001
 - Corporate certification: ISO 14001
 - Corporate certification: EN 1090
 - Corporate certification: EcoVadis
 - RoHS
 - REACH
 - The MUNK Group complies with a Code of Conduct
 - The Supply Chain Act does not apply due to our size
 - The materials used are listed in the technical specification
 - Resource-saving production: own photovoltaic systems
 - Energy-efficient consumption during production: LED lighting
 - Repairability, durability and quality: 15-year warranty on series products made in Germany
 - Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
 - Socially acceptable working conditions in production: fair wages, gender equality
 - Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
 - No health hazards for the users

More product pictures

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

