



Order no.: 110001

Scaling ladder lower section DIN EN 1147, wood

Specification

Rescue height 1.6 m	Intended use Rescue	Ladder length 2.67 m	Ladder length, 4 scaling ladders 8.4 m	Setting angle 70 °
Outer width	Ladder feet	Depth of side-rails	Width of side-rails	Step/Rung height
485 mm	Steel point	74.8 mm	36.7 mm	39 mm
Step depth	Number of steps/rungs	Step/Rung distance	Max. load capacity	Persons max.
21 mm	9 rungs	273 mm	216 kg	2
Material Wood	Weight 10.5 kg	Transport dimensions 2658 x 482 x 82 mm, 10.5 kg	Business division MUNK Rettungstechnik	Order no. 110001

Facts

- Rescue ladder compliant with DIN EN 1147
- Made of aluminium or wood
- Secure push-fit connections with spring-loaded locking pin
- Conical side-rail guide for safe stance



- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 216 kg / 2 people
- Side-rails made of finger-jointed pine or knotfree Oregon pine
- Rungs made of knot-free ash
- Painted in a colourless varnish

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



