



Order no.: 110001

# Scaling ladder lower section DIN EN 1147, wood

### **Specification**

| Rescue height<br><b>1.6 m</b> | Intended use Rescue                     | Ladder length<br>2.67 m                                | Ladder length, 4<br>scaling ladders<br><b>8.4 m</b> | Setting angle 70 °     |
|-------------------------------|---|--|---|------------------------|
| Outer width 485 mm            | Ladder feet<br>Steel point              | Depth of side-rails <b>74.8 mm</b>                     | Width of side-rails <b>36.7 mm</b>                  | Step/Rung height 39 mm |
| Step depth<br>21 mm           | Number of steps/rungs<br><b>9 rungs</b> | Step/Rung distance<br>273 mm                           | Max. load capacity 216 kg                           | Persons max.<br>2      |
| Material<br><b>Wood</b>       | Weight<br><b>10.5 kg</b>                | Transport dimensions<br>2658 x 482 x 82<br>mm, 10.5 kg | Business division<br>MUNK<br>Rettungstechnik        | Order no.<br>110001    |

#### **Facts**

- Rescue ladder compliant with DIN EN 1147
- Made of aluminium or wood
- Secure push-fit connections with springloaded locking pin
- Conical side-rail guide for safe stance



- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 216 kg / 2 people
- Side-rails made of finger-jointed pine or knotfree Oregon pine
- Rungs made of knot-free ash
- Painted in a colourless varnish

#### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



## More product pictures







## **Corporate certifications**

on sustainability criteria









