

Order no.: 110007

Wooden folding ladder DIN EN 1147



Specification

| | | | | |
|---|--|--|--|-----------------------------|
| Intended use Access | Ladder length 3 m | Setting angle 70 ° | Clear width between rungs 265 mm | Outer width 90 mm |
| Ladder feet Steel point | Depth of side-rails 60 mm | Width of side-rails 45 mm | Step/Rung height 34 mm | Step depth 20 mm |
| Number of steps/rungs 9 rungs | Step/Rung distance 300 mm | Max. load capacity 150 kg | Persons max. 1 | Material Wood |
| Weight 9.5 kg | Transport dimensions 3267 x 90 x 60 mm, 9.5 kg | Business division MUNK Rettungstechnik | Order no. 110007 | |

Facts

- Wooden folding ladder
- Access ladder compliant with DIN EN 1147
- Collapsible design
- Side-rails made of finger-jointed pine or knot-free Oregon pine
- 9 rungs made of knot-free ash

- Wooden parts painted in colourless varnish
- End fixtures for insertion
- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 108 kg / 1 person

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

