

Order no.: 167100

**Mobile scaffolding,
1.35 × 1.80 m, with
inclined ascents.**

Platform height [mm]

2510



Specification

Working height 4.51 m	Scaffolding height 3.78 m	Platform height 2.51 m	Platform width 1.35 m	Platform length 1.8 m
Load capacity 2 kN/m²	Weight 118 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation not possible	Outdoor use, central installation possible & allowed
Outdoor use, lateral installation not possible	Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, outdoor, central installation 120 kg	Business division MUNK Günzburger Steigtechnik	Article no. 167100
Price € 3,759.00	Notice Accessories necessary to fulfil DIN EN 1004-1:2021			

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- inclined steps from platform to platform with 100 mm deep, ribbed aluminium steps and handrail for safe ascent and descent as if on stairs

- All scaffolding parts are also available individually as spare or extension parts
- Also ideal for wall mounting or moving in narrow aisles
- Access through opening in the entry frame
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Large-format work area in width of 1.35 m
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Installation and removal without tools from platform to platform thanks to push-fit connectors and quick-release fasteners
- Easy to handle thanks to individual lightweight parts
- Different platform lengths available (1.80 / 2.45 / 3.0 m)
- Working heights up to 12.35 m
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²
- In order to meet the requirements of DIN EN 1004-1:2021, this scaffold must be retrofitted
- Option 1 - Conversion to MSG: 2 protective assembly railings telescopic (027991) are required for safe assembly, dismantling and conversion
- Option 2 - Conversion to SG: Replace the railings lengthwise with safety railings for mobile scaffoldings in the appropriate scaffold length (2 pieces per platform level). Replace the guardrail frame at the front (top platform level) with railing frame SG at the front in the appropriate width. Omit the diagonal braces above the first platform

Scope of supply

- Entry frame: 1 x
- Push-fit frame, 1.35 m.: 1 x
- Railing lengthwise: 2 x
- Platform with longitudinal flap: 1 x
- Platform without flap: 1 x
- Toe board front side: 2 x
- Toe board long side: 2 x
- Inclined ascent below: 1 x
- Top handrail for mobile scaffolding with inclined ascent: 1 x
- Diagonal brace: 1 x
- Horizontal strut: 2 x
- Swivel castor with spindle: 4 x
- Step-on bracket: 1 x
- Push-fit frame, 1.35 m.: 2 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



















Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant




Accessories

 <p>Order no.: 027992 Safety railing for mobile scaffolding</p>	 <p>Order no.: 027928 Entry frame</p>	 <p>Order no.: 027901 Push-fit frame, 1.35 m.</p>	 <p>Order no.: 027955 Railing lengthwise</p>	 <p>Order no.: 027970 Platform with longitudinal flap</p>
 <p>Order no.: 027932 Platform without flap</p>	 <p>Order no.: 027911 Toe board front side</p>	 <p>Order no.: 027943 Toe board long side</p>	 <p>Order no.: 027961 Inclined ascent below</p>	 <p>Order no.: 027939 Top handrail for mobile scaffolding with inclined ascent</p>
 <p>Order no.: 027937 Diagonal brace</p>	 <p>Order no.: 027935 Horizontal strut</p>	 <p>Order no.: 027917 Swivel castor with spindle</p>	 <p>Order no.: 027940 Step-on bracket</p>	 <p>Order no.: 027912 Ballast weight</p>



Order no.: 019081

Clip tray for tubes



Order no.: 027920

Wall spacer adjustable



Order no.: 070506

Frame extension can be clamped on




Order no.: 019274

Storage tray 500 x 220 mm




Order no.: 019276

Storage tray 800 x 300 mm



Order no.: 019175

Inspection sticker



Order no.: 019176

Inventory sticker




Order no.: 070508

Safety door on front side



Order no.: 070522

Scaffolding connector set



Order no.: 019136

Spring clip for mobile scaffolding




Order no.: 070524

Scaffolding strut telescopic




Order no.: 027104

Height-adjustable spindle



Order no.: 027922

Swivel castor with spindle, non-marking grey



Order no.: 027921

Swivel castor with spindle, electrically conductive



Order no.: 027958

Swivel castor



Order no.: 027902

Push-fit frame,
1.35 m.

Corporate certifications

on sustainability criteria

