



Order no.: 035312

**Rung straight ladder
made of glass-fibre
reinforced plastic /
aluminium with stabiliser**



Number of rungs

12 14

Specification

Working height 4.7 m	Step design Rungs	Number of steps/rungs 12 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Ladder length 3.58 m	Outer width 420 mm	Stabiliser width 930 mm	Depth of side-rails 58 mm
Width of side-rails 25 mm	Max. load capacity 150 kg	Design type To lean against	Weight 9.5 kg	Transport dimensions 3547 x 427 x 85 mm, 9.5 kg
Business division MUNK Günzburger Steigtechnik	Article no. 035312	Price € 712.00		

Facts

- Rung straight ladder made of reinforced fibre glass/aluminium
- Side-rails made of reinforced fibre glass profiles (min. 10 years ageing resistance)
- Rectangular rungs grooved on both sides 30 x 30 mm, aluminium
- 4-fold edged rung-to-side-rail connection

- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested up to 1,000 V as per DIN EN 61478:2002 Clause 6.5.1 and A1:2004 Category 1 (corresponds to European Standard DIN EN 131-7)
- Stabiliser made of reinforced fibre glass with non-slip ladder shoes in optimal width for the selected product
- Note: Products with GRP content are excluded from exchange due to their sensitivity, the statutory warranty applies (resistance to ageing 10 years).

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part



Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Accessories



Order no.: 019326

Accessory package "TRBS kit"



Order no.: 019324

Accessory package "Secure footing"



Order no.: 019329

Accessory package "Ergonomics"



Order no.: 019328

Accessory package "Practical aids 2"



Order no.: 019309

Accessory package "Ladder head protection, complete set"




Order no.: 019900

Hook-in platform R13 for rung ladders



Order no.: 019910

Hook-in step R13 for rung ladders



Order no.: 019634

'roll-bar' retrofit kit



Order no.: 019100

Wall spacer for rung ladders



Order no.: 019114

Gutter bracket kit



Order no.: 011179

Ridge bracket



Order no.: 019280

Attachable section "Window cleaner"



Order no.: 019902

MaxxStep step module



Order no.: 019287

Tool bag



Order no.: 019115

Bucket hook



Order no.: 019199

Outside shoe for cross-tube



Order no.: 019154

Information sticker for rung straight ladders over 3 m (stabiliser)



Order no.: 019176

Inventory sticker



Order no.: 019175

Inspection sticker



Order no.: 030296

Push-fit handrail for rung/step spacing 280/263 mm



Order no.: 030297

Push-fit handrail for rung/step spacing 280/263 mm



Order no.: 040344

Ladder head protection, magnet

Spare parts



Order no.: 019154

Information sticker for rung straight ladders over 3 m (stabiliser)

Certificates



17KFP1941-02 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-
3:2007
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK
EK5/AK1 17-1:2017
DIN EN 131-1:2016
DIN EN 131-2:2017

Corporate certifications

on sustainability criteria

