

Order no.: 044606

## Step shelf ladder, mobile for double shelf



Number of steps

- 6
- 7
- 8
- 9
- 10
- 11
- 12

### Specification

Working height <b>2.65 m</b>	Step design <b>Steps</b>	Number of steps/rungs <b>6 steps</b>	Step width <b>350 mm</b>	Step depth <b>80 mm</b>
Step/Rung distance <b>235 mm</b>	Vertical hook-in height <b>1.5 m</b>	Ladder length <b>1.78 m</b>	Base area <b>660 mm</b>	Inclination <b>70 °</b>
Outer width <b>400 mm</b>	Castor diameter <b>80 mm</b>	Max. load capacity <b>150 kg</b>	Design type <b>With castors   Mobile</b>	Weight <b>15.04 kg</b>
Transport dimensions <b>1873 x 580 x 156 mm, 6.94 kg</b>	Transport dimensions 2 <b>1390 x 45 x 45 mm, 2.98 kg</b>	Transport dimensions 3 <b>400 x 198 x 155 mm, 2.56 kg</b>	Transport dimensions 4 <b>400 x 198 x 155 mm, 2.56 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>
Order no. <b>044606</b>	Price <b>€ 860.00</b>			

### Facts

- Step shelf ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection
- For double shelves with aisle widths up to 1.60 m (variations up to 20 mm are compensated for by the chassis)

- Ladder easy to move thanks to smooth-running roll-top
- Self-locking spring-loaded castors, Ø 80 mm, at the lower end
- Non-slip ladder shoes
- Step spacing: 235 mm
- Ladder width: 400 mm (without castors)
- Ladder width with castors: 580 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- Note: Shelf ladders are manufactured in standard lengths stated here as well as individually made to measure. Please indicate the exact vertical hook-in height – the price includes the next higher ladder and a flat rate for changes of 51.00 euros RRP excluding VAT. Shelf ladders made to size are non-returnable

### Scope of supply

- Instructions for use and operation: 1 x
- Spring-loaded castor: 2 x
- Ladder: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality

- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures



## Added value

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Rail system

- Made-to-measure production of the rail system
- Easy assembly of all components



### Versatile solutions

- Ladders available in standard lengths or individual dimensions
- Available with and without roll-top as well as a rotatable version
- Optional spring-loaded castors
- For single and double-sided shelves



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9109612548

