



Order no.: 070501

## Modular de-icing system, stationary

Module types



### Specification

Platform length 1.27 m	Platform width 860 mm	Platform height 3 m	Height 4.1 m	Total width 960 mm
Railing height 1.1 m	Weight 70 kg	Transport dimensions 1270 x 860 x 4100 mm, 88 kg	Business division MUNK Günzburger Steigtechnik	Order no. 070501
Price € 2,333.00				

### Facts

- For the safe and quick removal of ice and snow loads from trucks and commercial vehicles. Also ideal for repairs to truck tarpaulins and superstructures.
- Maintenance-free design made of corrosion-resistant aluminium profiles and stainless steel connecting parts for stationary installation
- Individual total lengths and configurations possible thanks to efficient modular design

- Step and platform surfaces made of non-slip steel grating (R12) for all weather conditions. The hole pattern also prevents the accumulation of dirt, snow and water
- Convenient access to the walkway via 45° stairway with handrails on both sides and automatically closing safety door
- Railings on both sides with foot and knee boards ensure a high level of safety at work (height: 1,100 mm)
- Easy installation thanks to delivery in pre-assembled modules including assembly instructions
- The design takes account of DIN EN ISO 14122-2 and -3
- Maximum load: 1.5 kN/m<sup>2</sup>, step load 150 kg, total load 300 kg

### Scope of supply

- Support frame: 1 x
- Garde-corps: 2 x
- Platform: 1 x
- Railing connection: 2 x
- Installation material: 1 x
- Assembly instructions and instructions for use: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

### Product configurator

Configuring, enquiring about and ordering individual products could not be easier with our [product configurator](#) for stairs, bridging steps and mobile platform stairs. Simply enter your required dimensions and versions step by step, and a rotating 3D model will appear in real time. To save your configuration and request a quotation requires a login which will be set up for you by our Sales team.



### Safety railing

- Railings and handrails on both sides ensure a high level of safety at work
- Fixed size or telescopic safety door



### Modular kit system

- Individually and cost-efficiently combinable for the respective requirement
- Platform heights from 1.25 to 3.0 m
- Three different platform lengths can be selected

### Ascent

- Non-slip designs for secure footing
- All kinds of different materials can be selected with non-slip classes from R 9 to R 13 – suitable for the specific application purpose



## Modular walkway systems

- For a wide range of indoor applications in production, warehouses, as access to machines, as a walkway along building walls or as practical access for de-icing commercial vehicles in the winter months
- Thanks to innovative modular construction, walkway systems can be assembled conveniently, cost-effectively and yet precisely to meet individual requirements
- The platform height of the walkway systems can be individually determined between 1.25 and 3.0 metres. The desired total length is achieved by way of combining three different walkway lengths
- The modules can be easily assembled using pre-assembled modules, securely connected to one another and fastened to the underlying surface using foot brackets
- The maintenance-free modules are manufactured as a stable, corrosion-resistant aluminium construction with a supporting frame.
- Maximum load: 1.5 kN / m<sup>2</sup>, step load 150 kg, total load 300 kg
- Access to the walkway conveniently via stairs 45° with handrails on both sides and automatically closing safety door.
- The delivery from the factory is made in pre-assembled modules for quick and simple assembly in accordance with the enclosed assembly instructions

## Note

When assembling a walkway, only modules with the same platform height can be combined. Please contact us if you need different platform heights on a walkway system. This also applies if you need walkway systems for outdoor use, as they are primarily designed for indoor use (with the exception of de-icing systems).

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

