



Order no.: 019708

Retrofit kit clip-step for MaxxStep step module

Length [mm]

286 351 408 494 580

Specification

Product type Accessories	Length 286 mm	Width 85 mm	Height 23 mm	Step depth 80 mm
Set for ladders with 1 step	Number of step paddings in the set 1 pcs.	Type of non-slip protection clip-step	Material Plastics	Weight 0.12 kg
Transport dimensions 288 x 91 x 22 mm, 0.116 kg	Business division MUNK Günzburger Steigtechnik	Order no. 019708	Price € 14.00	

Facts

- Suitable for rung ladders made of aluminium and reinforced fibre glass
- For ergonomic, comfortable and fatigue-free standing when working in accordance with TRBS 2121 Part 2
- Can be mounted flexibly on any rung up to the last accessible rung (not with Rung Safe R 13)
- Quick and tool-free installation thanks to double clamping screws with locking device
- Can optionally be equipped with clip-step step padding, clip-step R13 and clip-step relax
- Available in different lengths



Scope of supply

- Clip-step step padding: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



