



Order no.: 041623

Single-sided stepladder with clip-step R13



Number of steps

- 3**
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 12
- 14

Specification

Working height 2.7 m	Step design Steps	Number of steps/rungs 3 steps	Platform included as step Yes	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection clip-step R13	Height 1.34 m	Platform height 670 mm	Base spread 700 mm
Inclination 70 °	Lower outer width 470 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm
Max. load capacity 150 kg	Design type Freestanding Single-sided access	Weight 5.75 kg	Transport dimensions 1434 x 461 x 164 mm, 5.751 kg	Business division MUNK Günzburger Steigtechnik
Article no. 041623	Price € 234.00			

Facts

- Step ladder made of aluminium
- Stable rectangular tube side-rails

- 80 mm deep grooved steps and large platform
- 4-fold edged step-to-side-rail connection
- 'safe-cap' ladder joint
- Conical side-rail guide for safe stance
- ergo-pad® grip area with clamping mechanism
- nivello® ladder shoes with patented 2-axis inclination technology
- Practical storage tray with integrated hooks and tool holders
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- clip-step R13 step padding for certified non-slip protection

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems

- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



The movable ladder shoe sets new standards in stability


[Learn more](#)



clip-step R 13 step padding


Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)




ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point




Accessories




Order no.: 019325

Accessory package "Secure footing outdoors"




Order no.: 019839

Wall-mounted ladder holder L




Order no.: 019810

Transport lifting castor for double-sided step ladders




Order no.: 019219

nivello® foot plate, electrically conductive




Order no.: 019213

nivello® foot plate for gratings 126 x 89 mm




Order no.: 019211

nivello® foot plate for smooth surfaces




Order no.: 019224

nivello® foot plate, claw




Order no.: 019115

Bucket hook




Order no.: 019846

Screw-on castors




Order no.: 019847

Screw-on castors




Order no.: 019940

Ground spikes for ladders with nivello ladder shoe




Order no.: 019915

Side-rail extension for ladder side-rail




Order no.: 019215

nivello® inside shoe, electrically conductive



Order no.: 019216

nivello® inside shoe, electrically conductive



Order no.: 019176

Inventory sticker



Order no.: 019175
Inspection sticker

Spare parts



Order no.: 019412
Corner strut for aluminium double-sided step ladders.



Order no.: 019845
Storage tray for double-sided step ladder



Order no.: 019209
nivello® foot plate, standard



Order no.: 019051
ergo-pad® grip area type 1



Order no.: 019205
nivello® inside shoe



Order no.: 019206
nivello® inside shoe



Order no.: 019142
Information sticker for double-sided ladders with single-sided access



Order no.: 041540
Retrofit kit clip-step R13 for double-sided step ladder, with single-sided access

Certificates



17KFP0689-04 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-
3:2007
EK5-AK1 17-
02:2017
DIN EN 131-1:2016
DIN EN 131-2:2017
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK

Corporate certifications

on sustainability criteria

