



Order no.: 062235

Back protection hoop strut, 3,000mm long

Material

Aluminium

Anodised aluminium

Stainless steel

Galvanised steel / hot dip galvanised steel

Specification

| Length 3 m | Material Aluminium | Weight 1 kg | Transport dimensions 3000 x 28 x 20 mm, 1 kg | Business division MUNK Günzburger Steigtechnik |
|------------------------------|------------------------------|----------------|--|--|
| Article no. 062235 | Price € 50.00 | | | |

Facts

- Enhances safety during ascent and descent of ladders
- For use in demanding environments
- Back protection hoop strut, 3,000 mm long
- C-connector rear protection struts can be ordered separately

Scope of supply

■ Brace: 1 x



Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning


- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All **fixed ladders / vertical ladders** at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders on buildings
- DIN 14094-1: Multiple-flight emergency ladder systems (emergency ladders)
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders on machinery

Accessories





Corporate certifications

on sustainability criteria









