



Order no.: 036404

Double-sided rung ladder GFRP



Number of rungs

2x4

2x5

2x6

2x8

2x10

2x12

2x14

Specification

Working height 2.5 m	Step design Rungs	Number of steps/rungs 2x 4 rungs	Step/Rung height 29 mm	Step depth 28 mm
Step/Rung distance 280 mm	Height 1.21 m	Ladder length 1.27 m	Base spread 940 mm	Inclination 70 °
Lower outer width 480 mm	Depth of side-rails 73 mm	Width of side-rails 25 mm	Max. load capacity 150 kg	Design type Freestanding Double-sided access
Weight 10 kg	Transport dimensions 1256 x 472 x 208 mm, 10 kg	Business division MUNK Günzburger Steigtechnik	Article no. 036404	Price € 648.00

Facts

- Double-sided rung ladder made of glass-fibre reinforced plastic
- Side-rails and rungs made of reinforced fibre glass plastic profiles (min. 10 years ageing resistance)
- Rectangular rungs grooved on both sides, 28 x 29 mm

- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- nivello® ladder shoes with patented 2-axis inclination technology
- Solid, galvanised steel hinges with screw attachment
- Plastic end caps on upper side-rail end
- Spreader lock with two high-strength polyester straps
- Rung distance: 280 mm
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested up to 28,000 V as per DIN EN 61475:2002 Category 1
- Note: Products with GRP content are excluded from exchange due to their sensitivity, the statutory warranty applies (resistance to ageing 10 years).

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems

- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

[Learn more](#)




Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.




Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)




Accessories




Order no.: 019326

Accessory package "TRBS kit"




Order no.: 019324

Accessory package "Secure footing"




Order no.: 019325

Accessory package "Secure footing outdoors"




Order no.: 019327

Accessory package "Practical aids 1"




Order no.: 019900

Hook-in platform R13 for rung ladders




Order no.: 019910

Hook-in step R13 for rung ladders




Order no.: 019219

nivello® foot plate, electrically conductive




Order no.: 019213

nivello® foot plate for gratings 126 x 89 mm




Order no.: 019211

nivello® foot plate for smooth surfaces




Order no.: 019209

nivello® foot plate, standard




Order no.: 019224

nivello® foot plate, claw




Order no.: 019841

XL wall-mounted ladder holder




Order no.: 019270

Storage tray for double-sided rung ladder



Order no.: 019176

Inventory sticker



Order no.: 019175

Inspection sticker

Spare parts



Order no.: 019140

Information sticker
for double-sided
ladders with
double-sided
access



Order no.: 019206

nivello® inside
shoe



Order no.: 019209

nivello® foot plate,
standard



Order no.: 019260

Ladder hinge for
solid plastic
ladders



Order no.: 019429

Spreader lock



Order no.: 019271

Tool tray for
double-sided rung
ladder

Certificates



17KFP1620-02 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-
3:2007
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK
EK5-AK1 17-
02:2017
DIN EN 131-1:2016
DIN EN 131-2:2017

Corporate certifications

on sustainability criteria

