



Order no.: 071337

Hinged loading bridge LB 300

Type

LB 300

LB 400

LB 500

Specification

Length 2.6 m	Total length max. 2.92 m	Extendable No	Foldable Yes	Total width 1.05 m
Clear width 1 m	Bridgeable distance 2.4 m	Material Aluminium	Permissible total load 500 kg	Surface Aluminium corrugated
Toe board height 63 mm	Mobile No	Wheelchair accessible Yes	Weight 67 kg	Business division MUNK Rettungstechnik
Order no. 071337				

Facts

- Loading bridge made of non-slip grooved aluminium
- Can be folded in the middle for space-saving transport

- For safe loading and unloading of vehicles and trailers
- With side toe boards
- For professional use

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

