



Order no.: 116121

Telescopic tear hook

Specification

| | | | | |
|--|---------------------------------|--|---|--|
| Material Aluminium coated | Extended length 3.2 m | Extended length with extension 4.8 m | Weight with extension 7.75 kg | Voltage protection max. 1000 V |
| Business division MUNK Rettungstechnik | Article no. 116121 | | | |

Facts

- Handle made of aluminium section
- Gradually telescoping
- Optional extension (part no. 116122) available
- Pulling force of 2.5 kN in lengthways direction
- Captive screws that can be operated without tools for locking or securing
- Cover caps captive with rope
- Non-slip grip and cold protection
- Protection against voltages up to max. 1,000 volts
- Built-in brake system for controlled retraction

- With protective cover in RAL 3000


Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Accessories



Corporate certifications

on sustainability criteria

