

Order no.: 068239

Connecting brace



Specification

Length 1 m	Material Stainless steel	Weight 2.5 kg	Transport dimensions 1000 x 70 x 40 mm, 2.5 kg	Business division MUNK Günzburger Steigtechnik
Article no. 068239	Price € 161.00			

Facts

- For reinforcing ladder sections if, contrary to the standard, the spacing of the wall anchors is larger than 2.0 m for construction reasons
- Made of stainless steel
- Two stuccos are required per ladder connection point
- If the back guard is mounted in the area of the connecting struts, clamps Clamps order no. 68240 are required

Scope of supply

- Brace: 1 x
- Installation material: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning


- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All **fixed ladders / vertical ladders** at a glance:

- [Single-flight vertical ladders](#) in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders [on buildings](#)
- DIN 14094-1: Multiple-flight [emergency ladder systems \(emergency ladders\)](#).
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders [on machinery](#).

Accessories



Corporate certifications

on sustainability criteria

