

Order no.: 068249

Wall anchor, rigid, 200 mm, stainless steel



Specification

Wall distance 200 mm	Material Stainless steel	Weight 0.98 kg	Transport dimensions 235 x 115 x 60 mm, 0.98 kg	Business division MUNK Günzburger Steigtechnik
Order no. 068249	Price € 42.00	Spare part for article no. 530105	Spare part for article no. 530110	Spare part for article no. 530100
Spare part for article no. 530125	Spare part for article no. 530115	Spare part for article no. 530120		

Facts

- Optimum stability thanks to rigid design
- Ideal for vertical ladders
- Wall anchor



Scope of supply

Wall anchor: 1 x

Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All fixed ladders / vertical ladders at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders <u>on buildings</u>
- DIN 14094-1: Multiple-flight <u>emergency ladder</u> <u>systems (emergency ladders)</u>
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders <u>on machinery</u>



Corporate certifications

on sustainability criteria



