



Order no.: 077583

## Rail slip-on device

Rail material

Aluminium

Stainless steel / Galvanised steel

### Specification

|  |  |                                  |  |                          |
|--|--|----------------------------------|--|--------------------------|
| Length<br><b>215 mm</b>                                      | Width<br><b>30 mm</b>  | Suitable for<br><b>Aluminium</b> | Material<br><b>Stainless steel V4A</b> | Weight<br><b>0.98 kg</b> |
| Transport dimensions<br><b>215 x 57 x 30 mm,<br/>0.98 kg</b> | Business division<br><b>MUNK Günzburger<br/>Steigtechnik</b> | Order no.<br><b>077583</b>       | Price<br><b>€ 129.00</b>               |                          |

### Facts

- For entry aid
- Made of V4A stainless steel
- Can be screwed to the top rail

#### Scope of supply

- Rail slip-on device: 1 x
- Installation material: 1 x
- Assembly instructions: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

