

Order no.: 064183

## Roof parapet bridge stainless steel special length



Length [mm]

**1200** 1400 1600

### Specification

Length <b>1.2 m</b>	Ladder length <b>1.22 m</b>	Ladder length incl. exit side-rail <b>2.21 m</b>	Entry/Exit <b>Roof parapet bridge</b>	Material <b>Stainless steel</b>
Passage width <b>536 mm</b>	Clear length <b>1.08 m</b>	Weight <b>56 kg</b>	Transport dimensions <b>2220 x 1200 x 590 mm, 63.1 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>
Article no. <b>064183</b>	Price <b>€ 3,556.00</b>			

### Facts

- With grating
- Passage width 536 mm, special widths on request
- Recommendation for the bottom end at the exit point: Adjustable wall anchors or foot plates
- Descent ladder: Length 1,220 mm, Length to be cut to size by client
- Longer delivery times thanks to order-related production

### Scope of supply

- Grating: 1 x
- Garde-corps: 2 x
- Descent ladder: 1 x
- Assembly kit: 1 x
- Assembly instructions: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures

---



## Added value

---

### Optimum planning

- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All [fixed ladders / vertical ladders](#) at a glance:

- [Single-flight vertical ladders](#) in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders [on buildings](#)
- DIN 14094-1: Multiple-flight [emergency ladder systems \(emergency ladders\)](#).
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders [on machinery](#).

## Accessories



Order no.: 062180

Mounting kit  
ballast for parapet  
crossings



Order no.: 060960

Exit railing, side



Order no.: 060962

Toe board for  
lateral exit railing



Order no.: 060986

Extension spacer  
mounting kit



Order no.: 060964

Exit railing, side



Order no.: 060966

Toe board for  
lateral exit railing



Order no.: 060968

Exit railing, side



Order no.: 063500

Safety barrier



Order no.: 063502

Safety doors  
without fall  
protection rail



Order no.: 063253

Ground  
attachment for  
base plate



Order no.: 068253

Ground  
attachment for  
base plate



Order no.: 063249

Rigid wall anchor  
200 mm,  
galvanised steel



Order no.: 063250

Wall anchor,  
adjustable, 165-  
205 mm,  
galvanised steel



Order no.: 063262

Wall anchor w.  
Clamping bracket,  
adjustable, 215-  
275 mm,  
galvanised steel



Order no.: 063261

Wall anchor w.  
clamping bracket,  
adjustable 275-  
375 mm,  
galvanised steel



Order no.: 063269

Wall anchor w. clamping bracket, adjustable 375-500 mm, galvanised steel



Order no.: 063270

Special wall bracket, adjustment range 500-600mm, galvanised steel



Order no.: 063271

Special wall bracket, adjustment range 600-700mm, galvanised steel



Order no.: 063272

Special wall bracket, adjustment range 700-800mm, galvanised steel



Order no.: 063273

Special wall bracket, adjustment range 800-900mm, galvanised steel



Order no.: 064270

Special wall bracket, adjustment range 500-600mm, stainless steel



Order no.: 064271

Special wall bracket, adjustment range 600-700mm, stainless steel



Order no.: 064272

Special wall bracket, adjustment range 700-800mm, stainless steel



Order no.: 064273

Special wall bracket, adjustment range 800-900mm, stainless steel



Order no.: 063257

Wall anchor U-bracket, rigid



Order no.: 063259

Wall anchor U-bracket, rigid



Order no.: 063263

Wall anchor U-bracket, adjustable, 165-205 mm, galvanised steel



Order no.: 063260

Wall anchor U-bracket, adjustable, 200-275 mm, galvanised steel



Order no.: 063267

Wall anchor U-bracket, adjustable, 275-375mm, galvanised steel



Order no.: 063275

Wall anchor U-bracket, adjustable, 375-500 mm, galvanised steel

## Corporate certifications

---

on sustainability criteria

